

PRODUCT - HOGSNOT MUSCLE CAR SAE 20W-50

MATERIAL SAFETY DATA SHEET

PRODUCT - HOGSNOT MUSCLE CAR SAE 20W-50

October 21, 2008

Section 1 **Product & Company Information**

HOGSNOT LUBRICANTS CO. INTL **MANUFACTURER**

3175 MARTIN RD.

COMMERCE TWP, MI, 48390

PHONE NUMBERS **General Information** (866) 939-7668

Emergency (Chemtrec) (800) 424-9300

CHEMICAL FAMILY Petroleum Hydrocarbon; Blend Stock

CHEMICAL NAME Mixture

PRODUCT CODE LHS3010, LHS3015

CHEMICAL FORMULA Mixture

Mixture (Refer to Section 2) **CAS NUMBER**

SYNONYMS Motor Oils, Petroleum Lubricating Oils

Section 2 **Composition / Information on ingredients**

Note: See section 8 for occupational exposure limits and section 11 for LC50/LD50 INFORMATION.

Ingredient Name CAS No. Conc. (%w/w) Mineral Oil Mixture 70-85 **Proprietary Additives** Mixture 10-18 68649-42-3

Contains - Zinc dialkyl dithiophosphate

-Unlisted proprietary Anti-friction blend

VI Improver Mixture 5-12

Section 3 **Hazards Identification**

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments. Not classified as hazardous according to the criteria of NOHSC nor classified as dangerous goods according to the ADG Code.

Primary Hazards and Critical Effects

Environmental Hazards

: Not classified as dangerous for the environment according to EC criteria.

Hazardous Material Information System (U.S.A.)





PRODUCT – HOGSNOT MUSCLE CAR SAE 20W-50

Section 4 First-Aid Measures

Inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get

medical attention if symptoms appear.

Ingestion : If affected person is fully conscious, give one glass of water to drink. Never give anything by mouth to an

unconscious person. Get medical attention if symptoms appear.

Skin Contact : Wash with soap and water. Get medical attention if irritation develops.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention

immediately.

Section 5 Fire Fighting Measures

Extinguishing Media : In case of fire, use water spray (fog), foam, dry chemical, or CO2.

Fire-Fighting Procedures : Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout

gear.

Flash point : Open cup 234°C (453F) (Cleveland)

Section 6 Accidental Release Measures

Personal Precautions: Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (section 8). Follow all fire-fighting procedures (section 5).

Environmental : If Precautions and Clean-up Methods

If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion-proof means to transfer material to a sealable, appropriate container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Minimize contact of spilled material with soils to prevent runoff to surface waterways.

Note: See section 1 for emergency contact information and section 13 for waste disposal.

Section 7 Handling & Storage

Handling : Wash thoroughly after handling.

Storage : Keep container tightly closed. Keep container in a cool, well-ventilated area.

Section 8 Exposure Controls and Personal Protection

Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Personal Protective Equipment

Respiratory System : Use appropriate respiratory protection if there is the potential to exceed the exposure limit(s).

Skin and Body : Disposable outer garments when there is the potential for contact with the material.

Hands : Use chemical resistant, impervious gloves.

Eyes : Safety glasses with side shields. Goggles with a face shield may be necessary depending on quantity of

OEL Canada

material and conditions of use.

States). TWA: 5 mg/m³

OEL United States

Occupational Exposure Limits

Occupational Exposure Limits

Ingredient Name

1) Mineral Oil

ACGIH (United TWA: 5 mg/m³ EH40 (UK) (Europe, 2002). 2003).

TWA: 5 mg/m³ STEL: 10 mg/m³ TWA: 5 mg/m³ 8 hour/hours.

OSHA (United TWA: 5 mg/m³ EH40 (UK) (Europe, 2003). TWA: 5 mg/m³ 8 hour/hours.

OEL Europe

OEL Australia



PRODUCT – HOGSNOT MUSCLE CAR SAE 20W-50

Section 9 Physical and Chemical Properties

Physical State and

Appearance : Liquid & Dark Brown w/green tint

 Vapor Density
 : Not determined

 Solubility
 : Insoluble in cold water

 Auto-Ignition Temperature
 : Not determined

Flash Point : Open cup 234°C (453F) (Cleveland)
Viscosity : 17.4 cSt @ 100°C - (153 cSt @ 40°C)

Section 10 Stability and Reactivity

Stability : The product is stable.

Materials to avoid : Strong oxidizing and reducing agents.

Conditions to avoid : High temperatures, sparks, and open flames.

Section 11 Toxicological Information

Routes of Entry : Skin, Eyes, Ingestion, and Inhalation.

Target Organs ; None known.

Acute Effects

Inhalation :

Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation.

Ingestion : Not determined.

Skin Contact :

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in

non-allergic contact dermatitis and absorption through the skin.

Eye Contact : Non-irritating to the eyes.

Chronic Effects

Adverse Effects : Not determined.

Toxicity Data

Ingredient Name Test Result Route Species

Not determined.

Other information : Not available.

Section 12 Ecological Information

Environmental Hazards : Not classified as dangerous for the environment according to EC criteria. Based on calculation.

Environmental Fate : This product contains components which may be persistent in the environment.

Section 13 Disposal Considerations

Waste Handling and Disposal

: Waste must be disposed of in accordance with federal, state and local environmental control regulations.



PRODUCT – HOGSNOT MUSCLE CAR SAE 20W-50

Section 14 **Transportation Information**

Regulatory Information	UN number	Proper shipping name	Class	Packing Group	Label	Additional information
	Not regulated.	-	-	-		-
	Not regulated.	-	-	-		-
ADR/RID Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		-
ADG Class	Not regulated.	-	-			-

Notice to Reader

The above transport information is provided to assist in the proper classification of this product and may not be suitable for all shipping conditions.

Section 15 **Regulatory Information**

US Regulations

SARA 313 toxic chemical : No SARA 313 chemicals are present above the reporting threshold.

notification and release

reporting

SARA 311/312

Hazardous Categorization

RQ (Reportable quantity)

: SARA 311/312 Nuisance Mist/Dust Only

: CERCLA: Hazardous substances.: STYRENE: 1000 lbs. (453.6 kg);

Canadian Regulations

WHMIS (Classification) : Not a WHMIS controlled material.

EU Regulations

Risk Phrases : This product is not classified according to EU legislation.

Safety Phrases : Not applicable.

International Inventory Status

United States : All components on TSCA Inventory

Canada : All components on DSL

Europe : One or more components not found on EINECS, but on ELINCS

Japan : All components on METI Australia : All components on NICNAS Korea : All components on ECL : All components on IECSC China **Philippines** : All components on PICCS



PRODUCT - HOGSNOT MUSCLE CAR SAE 20W-50

Section 16 Other Information

Avoid prolonged skin contact with used motor oil. Prolonged contact with used motor oil has been shown to cause cancer in laboratory animals.

After draining oil, wash skin thoroughly with soap and water. Clean oil-soaked clothing before reuse.

Additional Notes:

This product is FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.

PREPARATION INFORMATION

Validated by MSDS Author on 10/21/2008

Notice to Reader

HogSnot Lubricants Co. Intl., believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. No warranty or fitness for any particular purpose, warranty of merchantability, or any other warranty expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and of the information referred to herein are beyond the control of HogSnot Lubricants Co. HogSnot expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

ADDRESS CONTACT INFORMATION

HOGSNOT LUBRICANTS CO. 3175 MARTIN RD. COMMERCE TWP, MI, USA 48390 866-939-7668